

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A two-way satellite communication system, comprising:
a transceiver configured to transmit signals over a plurality of return channels to a satellite and to receive signals over a downlink channel from the satellite;
a network control cluster (NCC) configured to dynamically manage available bandwidth associated with the plurality of return channels during transmission;
a burst channel demodulator (BCD) coupled to the NCC and configured to demodulate the signals that are received from each of the plurality of return channel; and
a hub configured to communicate with the transceiver over the plurality of return channels, wherein the hub provides connectivity between the transceiver and a packet switched network.
2. (previously presented) The system according to claim 1, wherein the transceiver transmits the signals over the plurality of return channels using a plurality of carriers, each of the carriers being a Time Division Multiple Access (TDMA) stream.
3. (original) The system according to claim 1, wherein the packet switched network is the Internet.
4. (original) The system according to claim 1, wherein the packet switched network is an Internet Protocol (IP) network.
5. (original) The system according to claim 1, further comprising:
a user terminal coupled to the transceiver and configured to generate data for transmission over the packet switched network; and

an antenna coupled to the transceiver.

6. (original) The system according to claim 1, wherein the user terminal is configured to perform auto-commissioning via a temporary channel to the satellite.

7. (original) The system according to claim 6, wherein the user terminal couples to the transceiver through a Universal Serial Bus (USB).

8. (original) The system according to claim 1, wherein the transceiver supports IP multicasting.

9. (canceled)

10. (original) The system according to claim 1, wherein the transceiver supports IP multicasting.

11. (original) The system according to claim 1, wherein the signals represent packets that includes a Medium Access Control (MAC) address that is based upon traffic type.

12. (previously presented) A method for exchanging frames over a two-way satellite communication system, the method comprising:

establishing connection to a packet switched network;

dynamically assigning bandwidth provided over a plurality of return channels to a plurality of remotes;

communicating the frames over a respective return channel to a satellite;

determining is sufficient bandwidth is allocated to each communicating channel;

sending data via ALOHA channels to dynamically allocate additional bandwidth if the determining step establishes that insufficient bandwidth exists; and

generating signals associated with the frames using a plurality of carriers, each of the carriers being a Time Division Multiple Access (TDMA) stream.

13. (original) The method according to claim 12, wherein the transmitting step is performed by a transceiver.

14. (canceled)

15. (original) The method according to claim 12, wherein the packet switched network in the establishing step is the Internet.

16. (original) The method according to claim 12, wherein the packet switched network in the establishing step is an Internet Protocol (IP) network.

17. (previously presented) The method according to claim 12, further comprising: generating data for transmission over the packet switched network via the respective return channel.

18. (original) The method according to claim 17, further comprising: performing auto-commissioning over a temporary channel to the satellite.

19. (original) The method according to claim 17, wherein the step of generating data is performed by a
user terminal, the user terminal coupling to a transceiver through a Universal Serial Bus (USB).

20. (original) The method according to claim 13, wherein the transceiver supports IP multicasting.

21. (previously presented) The method according to claim 12, further comprising:
demodulating signals corresponding to the frames that are received from the return channel.

22. (original) The method according to claim 12, wherein the frames in the
transmitting step includes a Medium Access Control (MAC) address that is based upon traffic
type.

23. (currently amended) A two-way satellite communication system for exchanging
frames, the system comprising:

means for transmitting frames over a plurality of return channels to a satellite and to
receive signals over a downlink channel from the satellite;

means for dynamically managing available bandwidth associated with the plurality of
return channels during transmission;

means for demodulating the signals that are received from each of the plurality of return
channel, said means for demodulating being communicatively coupled to the means for
dynamically managing bandwidth; and

means for communicating with the transmitting means over the plurality of return
channels, wherein the communicating means provides connectivity between the transmitting
means and a packet switched network.

24. (original) The system according to claim 23, wherein the transmitting means is a
transceiver.

25. (original) The system according to claim 24, further comprising: means for
generating signals associated with the frames using a plurality of carriers, each of the carriers
being a Time Division Multiple Access (TDMA) stream.

26. (original) The system according to claim 23, wherein the packet switched
network is the Internet.

27. (original) The system according to claim 23, wherein the packet switched network is an Internet Protocol (IP) network.
28. (original) The system according to claim 24, further comprising: means for generating data for transmission over the packet switched network via the return channel.
29. (original) The system according to claim 28, further comprising: means for performing auto-commissioning over a temporary channel to the satellite.
30. (original) The system according to claim 28, wherein the generating means is a user terminal, the user terminal coupling to a transceiver through a Universal Serial Bus (USB).
31. (original) The system according to claim 24, wherein the transceiver supports IP multicasting.
32. (original) The system according to claim 23, further comprising: means for managing bandwidth associated with the return channel; and means for demodulating signals corresponding to the frames that are received from the return channel.
33. (original) The system according to claim 23, wherein the frames includes a Medium Access Control (MAC) address that is based upon traffic type.
34. (previously presented) A computer-readable medium carrying one or more sequences of one or more instructions for exchanging frames over a two-way satellite communication system, the one or more sequences of one or more instructions including instructions which, when executed by one or more processors, cause the one or more processors to perform the steps of:
- establishing connection to a packet switched network;

dynamically assigning bandwidth provided over a plurality of return channels to a plurality of remotes;

communicating the frames over a respective return channel to a satellite;

determining if sufficient bandwidth is allocated to each communicating channel;

sending data via ALOHA channels to dynamically allocate additional bandwidth if the determining step establishes that insufficient bandwidth exists; and

generating signals associated with the frames using a plurality of carriers, each of the carriers being a Time Division Multiple Access (TDMA) stream.

35. (original) The computer-readable medium according to claim 34, further comprising:

generating signals associated with the frames using a plurality of carriers, each of the carriers being a Time Division Multiple Access (TDMA) stream.

36. (original) The computer-readable medium according to claim 34, wherein the packet switched network in the establishing step is the Internet.

37. (original) The computer-readable medium according to claim 34, wherein the packet switched network in the establishing step is an Internet Protocol (IP) network.

38. (original) The computer-readable medium according to claim 34, wherein the one or more processors further perform the step of:

generating data for transmission over the packet switched network via the return channel.

39. (original) The computer-readable medium according to claim 34, wherein the one or more processors further perform the step of:

performing auto-commissioning over a temporary channel to the satellite.

40. (previously presented) The computer-readable medium according to claim 34, wherein the one or more processors further perform the step of:
demodulating signals corresponding to the frames that are received from the return channel.

41. (original) The computer-readable medium according to claim 34, wherein the frames in the transmitting step includes a Medium Access Control (MAC) address that is based upon traffic type.